


Service manual

Gear pumps - series GHD



jühstroj
AERO TECHNOLOGY & HYDRAULICS

1. Basic description

Gear pumps serve to transform mechanical energy into pressure energy of a liquid. The GHD-series pumps are designed primarily for use in mobile hydraulics in the areas of agricultural, heavy construction, and road machines, and in contemporary hydraulic systems of handling technique. They are produced in different versions of drives, fastening flanges and liquid intakes and discharges. These pumps conform to ISO, SAE, UNI, and other worldwide established standards; they may be delivered in one- or multiple-section versions. They may also be delivered as reversible pump. The basic version consists of several parts. The body, cover and flange pump are made of gray iron. For heavy-duty service with a charge of the driving shaft, the pump may be equipped with front-end roller bearings.

2. Table of parameters

Nominal Size Parameters		Symb.	Unit	GHD1-17	GHD1-22,5	GHD1-27	GHD1-29	GHD1-34
Nominal displacement		V_g	[cm ³]	17,389	22,461	27,533	28,982	34,054
Rotation speed	nominal	n_n	[min ⁻¹]	1500				
	minimum	n_{min}	[min ⁻¹]	400				
	maximum	n_{max}	[min ⁻¹]	3200			3000	
Pressure at the inlet port	minimum	p_{1min}	[bar]	-0,3				
	maximum	p_{1max}	[bar]	0,5				
Pressure at the outlet port	maximum continuous	p_{2n}	[bar]	290				280
	maximum	p_{2max}	[bar]	310				300
	peak	p_3	[bar]	320				310
Nominal flow rate (min.) at n_n and p_{2n}		Q_n	[dm ³ .min ⁻¹]	24,00	31,00	38,00	40,00	47,00
Maximum flow rate at n_{max} and p_{2max}		Q_{max}	[dm ³ .min ⁻¹]	54,00	69,70	85,50	84,30	99,10
Nominal input power (max.) at n_n and p_{2n}		P_n	[kW]	14,80	19,20	23,50	24,70	28,00
Max. input power at n_{max} and p_{2max}		P_{max}	[kW]	33,80	43,70	53,60	52,80	60,10

Nominal Size Parameters		Symb.	Unit	GHD1-43	GHD1-51	GHD1-61	GHD1-71
Nominal displacement		V_g	[cm ³]	43,473	51,443	61,587	71,006
Rotation speed	nominal	n_n	[min ⁻¹]	1500			
	minimum	n_{min}	[min ⁻¹]	400	350	250	
	maximum	n_{max}	[min ⁻¹]	2800	2600	2200	1800
Pressure at the inlet port	minimum	p_{1min}	[bar]	-0,3			
	maximum	p_{1max}	[bar]	0,5			
Pressure at the outlet port	maximum continuous	p_{2n}	[bar]	270	260	240	200
	maximum	p_{2max}	[bar]	290	280	260	220
	peak	p_3	[bar]	300	290	270	230
Nominal flow rate (min.) at n_n and p_{2n}		Q_n	[dm ³ .min ⁻¹]	60,00	71,00	85,00	98,00
Maximum flow rate at n_{max} and p_{2max}		Q_{max}	[dm ³ .min ⁻¹]	118,10	129,70	131,40	124,00
Nominal input power (max.) at n_n and p_{2n}		P_n	[kW]	34,50	39,30	43,50	41,80
Max. input power at n_{max} and p_{2max}		P_{max}	[kW]	69,20	73,40	69,10	55,10

Nominal Size Parameters		Symb.	Unit	GHD2-51	GHD2-61	GHD2-71	GHD2-82	GHD2-90
Nominal displacement		V_g	[cm ³]	51,810	61,231	71,828	82,426	90,668
Rotation speed	nominal	n_n	[min ⁻¹]	1500				
	minimum	n_{min}	[min ⁻¹]	400				
	maximum	n_{max}	[min ⁻¹]	3200		3000	2800	
Pressure at the inlet port	minimum	p_{1min}	[bar]	-0,3				
	maximum	p_{1max}	[bar]	0,5				
Pressure at the outlet port	maximum continuous	p_{2n}	[bar]	280		270	250	
	maximum	p_{2max}	[bar]	300		290	270	
	peak	p_3	[bar]	310		300	280	
Nominal flow rate (min.) at n_n and p_{2n}		Q_n	[dm ³ .min ⁻¹]	71,50	84,50	99,10	113,70	125,10
Maximum flow rate at n_{max} and p_{2max}		Q_{max}	[dm ³ .min ⁻¹]	160,80	190,10	223,00	239,90	246,30
Nominal input power (max.) at n_n and p_{2n}		P_n	[kW]	42,70	50,40	59,20	65,50	66,70
Max. input power at n_{max} and p_{2max}		P_{max}	[kW]	97,50	115,30	135,20	140,60	134,40

Nominal Size Parameters		Symb.	Unit	GHD2-100	GHD2-110	GHD2-125	GHD2-150	
Nominal displacement		V_g	[cm ³]	100,088	110,686	125,994	150,721	
Rotation speed	nominal	n_n	[min ⁻¹]	1500				
	minimum	n_{min}	[min ⁻¹]	350		250		
	maximum	n_{max}	[min ⁻¹]	2700	2600	2400	2000	
Pressure at the inlet port	minimum	p_{1min}	[bar]	-0,3				
	maximum	p_{1max}	[bar]	0,5				
Pressure at the outlet port	maximum continuous	p_{2n}	[bar]	230	210	190	170	
	maximum	p_{2max}	[bar]	250	230	210	190	
	peak	p_3	[bar]	260	240	220	200	
Nominal flow rate (min.) at n_n and p_{2n}		Q_n	[dm ³ .min ⁻¹]	138,10	152,7	173,9	208	
Maximum flow rate at n_{max} and p_{2max}		Q_{max}	[dm ³ .min ⁻¹]	262,10	279,2	293,3	292,4	
Nominal input power (max.) at n_n and p_{2n}		P_n	[kW]	67,70	68,4	70,4	75,4	
Max. input power at n_{max} and p_{2max}		P_{max}	[kW]	132,50	129,8	124,5	112,3	

3. Working liquid

- Mineral oils for hydraulic drives (NBR seal)
- Hydraulic liquids based on vegetable oils, suitable for hydrostatic drives (NBR seal)

3.1. Liquid temperature

- $t = -20 \div +80$ [°C] (NBR seal)
- 20 \div +120 [°C] (FKM seal)

3.2. Kinematic viscosity of liquid [$m^2 \cdot s^{-1}$]

- recommended (for continuous operation) 20.10⁻⁶ to 100.10⁻⁶
- maximum when put in operation (at kinematic viscosity 1200.10⁻⁶
>1000 allowed service pressure is <10 bar
speed < 1500 RPM)
- minimum (operating mode at 10.10⁻⁶ to 20.10⁻⁶ has to be 10.10⁻⁶
consulted with the producer)

3.3. Filtration coefficient β_α

- $\beta_{25} 75 \geq$ (for pressure $p_2 < 200$ bar)
- $\beta_{10} 75 \geq$ (for pressure $p_2 > 200$ bar)

3.4. Contamination level – class of liquid ISO 4406

- 19/16 (for pressure $p_2 < 200$ bar)
- 17/14 (for pressure $p_2 > 200$ bar)

3.5. Contamination level – class of liquid NAS 1638

- 10 (for pressure $p_2 < 200$ bar)
- 8 (for pressure $p_2 > 200$ bar)

4. Pump drive

Driving mechanism must cause neither the axial nor radial load of the pump shaft. In case of the operation with the load of the driving shaft, the pump must be equipped with the front-end bearing. The driving mechanism must meet the specified tolerances of the position, see the Figure No. 1. The usage of flexible coupling is recommended.

The tolerance of the driving mechanism position:




Figure No. 1

Coupling used for the of the torque transmission	flexible	solid
Y (mm)	0,1	0,04

5. Assembly / disassembly and service instructions

The gear pump can be installed on the final product in the arbitrary position. The external check of the pump must be done before its installation on the driving unit.

During handling, it is necessary to avoid damage of the flange seating face, of the spigot, of the end of driving shaft, possibly of the sealing faces at inlet and outlet.

The end of the driving shaft can be easily put into the catch cam until the pump flange face seats on the counterpart. If the pump's shaft has the spline end or claw where the permanent lubrication is not secured during operation, we recommend to lubricate it by the suitable grease on the assembly occasion.

Fix the pump to the counterpart by tightening the screws (nuts) after the pump's flange face has seated completely on the seating face of the counterpart (casing).

Remove the safety plugs of the inlet and outlet holes of all sections before connecting the pump to the hydraulic circuit. Check, whether the threads for connecting the hydraulic line are not damaged. During assembly, please, avoid the entering of impurities into the pump.

The seal on the flange face must be such arranged to prevent the oil leakage from the driving mechanism area through the pump's binder screws.

After connection, let the pump run at least 2 minutes without pressure at minimum speed and monitor whether it runs smoothly, without excessive heating. When hot oil enters the cold pump, do not load it before the whole unit is warmed up completely.

When dismantling the final product, protect the internal area by covering the connecting holes immediately.

The safety valve must be installed in the pump hydraulic circuit. The valve must be protected against incompetent manipulation. The valve is adjusted at the most on maximal permanent pump pressure. The peak pressure in the circuit must not exceed the allowed value. In case of multiple pumps, the safety valve must be installed in the circuit of each section.

The used oil quality must meet the relevant oil standard for the whole operation period and its specified cleaning must be ensured.

It must be ensured that the oil quantity in the hydraulic circuit will not drop under the value when, in the inlet branch area, the oil turbulence appears as well as the air intake and the temperature increase above the allowed limit. After pump installation into hydraulic circuit, and after any circuit dismantling, it is necessary to vent the whole system perfectly.

Hydraulic line – the intake line should have the nominal diameter specified such that at the viscosity $100 \cdot 10^{-6} \text{ m}^2 \cdot \text{s}^{-1}$ and at maximum flow, the pressure intake does not exceed the allowed values. The pressure line should have such nominal diameter that the liquid speed does not exceed $8 \text{ m} \cdot \text{s}^{-1}$.

Operation – the gear pumps do not need, during the operation, the special maintenance or service except the care of the working liquid and the regular inspections for detecting the possible leakage in joints and the checks of the pump binder screws (nuts) tightening. The oil change must be done with regard on the correct functioning of the whole hydraulic circuit. The working liquid change interval will be specified by the finalist on the base of the operation test.

6. Warehousing warranty period - (applicable to sales representatives only)

The manufacturer provides to Jihostroj sales representatives a 1 year warranty to sale the product to an operator. This period is not included in the service life of the product and is covered by the manufacturer's warranty.

Sales representatives are required to comply with the following conditions of warehousing:

Temperature: from -20°C to $+40^{\circ}\text{C}$

Humidity: from 40% to 80%

7. Service warranty period

The manufacturer provides to its customers a service warranty for the product in the range of 3000 hours for 2 years from the date of sale, whichever occurs earlier.

8. Validity of the commercial warranty

The manufacturer grants the commercial warranty and guarantees the quality of the product provided the operating conditions listed in the service manual are complied with.

The customer is required to present the "Complaint report" to make a claim, containing at least the following information: Type designation, serial number, description of the defect, number of service hours.

The product that is subject to a complaint must be sent to the factory complete, clean, with blinded sockets and with flange and drive protection installed. The pump conversion or other modifications are not allowed.

The claim will be rejected and the product will be repaired at the costs of the customer unless the above conditions will be met.

The manufacturer disclaims responsibility for any damage resulting from the incorrect installation and exploitation.



Jihostroj a.s Budějovická 148, 382 32 Velešín, Czech Republic
e-mail: mailbox@jihostroj.cz, [http: www.jihostroj.com](http://www.jihostroj.com)